

Data sheet P 530

Revision 12

1. CHEMICAL COMPOSITION

"P530" is a special nonmagnetic, austenitic Mn-Cr-N-steel with a Nickel-content of $\leq 2\%$.

С	Mn	Cr	Мо	Ν	Ni
max. 0,05	18,50-20,00	13,00-14,00	0,40-0,60	0,25-0,40	max. 2,00

2. MECHANICAL PROPERTIES

Following mechanical properties (tested at room temperature) are achieved by a special cold-working process over the full length of the collar:

Yield Strength (min.):	OD less than 4"	120 ksi	830 N/mm ²
0,2%-offset method	OD 4" to 9 ¹ / ₄ "	110 ksi	760 N/mm ²
	$OD 9^{1/2}$ and larger	100 ksi	690 N/mm ²
Tensile Strength	OD less than 4"	130 ksi	900 N/mm ²
	OD 4" and larger	120 ksi	830 N/mm ²
Elongation (mir	n.):	25%	25%
Reduction of area (mir	50%	50%	
Impact energy (min.):		90 ft.lb	122 J
Hardness Brinell: (mir	260-350 HB	260-350 HB	

3. MAGNETIC PROPERTIES Relative permeability: ≤ 1,001.

4. CORROSION RESISTANCE

- Transgranular SCC: Prevented by special surface treatments (Hammer peening, roller burnishing, shot peening).
- Intergranular SCC: The occurrence of material sensitization is prevented by quenching after warmforging. Each collar is tested according to ASTM A 262, Pract.A and E, last edition.

5. NON-DESTRUCTIVE TESTING

- Magnetic inspection: Drill collars are 100% tested by a proprietary probe-testing process using a Förster Magnetomat 1.782. ("Hot Spot"-test). Magnetic permeability of each collar is certified with the printout of probe-testing.
- **Ultrasonic inspection:** Each collar is ultrasonically inspected over 100% of the volume according to ASTM E 114, last edition as a minimum level.

6. GALLING RESISTANCE

"P530" is due to the chemical composition and the special coldworking process less susceptible to galling than Cr-Ni steels.

Non-Magnetic material optimized for MWD-collars and stabilizers (higher strength and endurance) is available on special request. P530-Non-Magnetic Drill Collars meet all requirements of API Spec. 7.1, last edition.
All tests are carried out according to ASTM-Standards, last editions.
Prepared / released: B. Holper
Date: June.. 2013